

## MATERIAL SAFETY DATA SHEET

### KEQI® POLYCARBONATE SHEET

Revision : 27/05/2015, Supersedes issue : 06/02/2002

Page : 1/4

#### 1. CHEMICAL PRODUCT & COMPANY IDENTIFICATION

##### MANUFACTURER / SUPPLIER

ZHEJIANG AOCI DECORATION MATERIALS CO., LTD.

No.2618, Haifeng Road, Binhai Industrial Zone,

Jiaojiang, Taizhou, Zhejiang,

China.

##### TELEPHONE

During office hours: +86-576-88124888 (24 hr) ; After office hours: +86-576-88121897 (24 hr).

PRODUCT IDENTIFIER : KEQI® POLYCARBONATE Sheet.

DESCRIPTION : Multi-wall polycarbonate (PC) thermoplastic sheet, with one side UV surface protection.

: Main polymer: Poly (bisphenol-A carbonate), CAS 24936-68-3.

PRODUCT USE : As sheet for flat and curved glazing applications.

#### 2. COMPOSITION / INFORMATION ON INGREDIENTS

This product consists primarily of high molecular weight polymers which are not expected to be hazardous.

#### 3. HAZARDS IDENTIFICATION

##### POTENTIAL HEALTH EFFECTS

Eyes : Small particles may cause irritation / injury due to mechanical action.

Skin : Product not likely to cause skin irritation.

Ingestion : Not acutely toxic.

Inhalation : Product inhalation unlikely due to physical form.

Melt processing health : Molten plastic can cause severe burns.

effects : Processing fumes may cause irritation to the eyes, skin and respiratory tract, and in cases of severe over-exposure, nausea and headache.

Medical restrictions : When heated up to processing temperatures virtually all thermoplastics emit processing fumes. The exact composition and concentration of these processing fumes depend on the sheet formulation, including additives, the residence time in the processing equipment, equipment variables such as venting parameters and the processing temperature. When the product is processed according To our recommended guidelines (available on request) and

## KEQI® POLYCARBONATE SHEET

Revision : 27/05/2015, Supersedes issue : 06/02/2002

Page : 2/4

taking normal precautions detailed below, there are no known adverse effects to human health. Certain sensitive individuals and those with respiratory impairments, however, may experience some temporary irritation by exposure to specific components in the processing fumes.

### 4. FIRST AID MEASURES

Eyes	: Remove contact lenses at once. Immediately flush eyes well with copious quantities of water or normal saline solution for 20-30 minutes. If irritation persists, seek medical attention.
Skin	: No first aid required.
Ingestion	: Since this material is not expected to be an ingestion problem, no first aid procedures are required.
Inhalation	: Not likely to be inhaled due to physical form.
Thermal processing	: For molten plastic skin contact, cool rapidly with water and seek immediate medical attention. Do not attempt removal of plastic without medical assistance. Do not use solvent for removal. : For processing fume inhalation irritation, leave contaminated area and breathe fresh air. If coughing, difficulty in breathing or any other symptoms develop, seek medical attention at once.

### 5. FIRE FIGHTING MEASURES

Fire fighting	: Approved pressure demand breathing apparatus and protective clothing should be used for all fires. : This product will melt but will not be carried on the surface of water.
Extinguishing media	: Water spray and foam are recommended. Water is the best extinguishing medium. : Carbon dioxide and dry chemical are not generally recommended because their lack of cooling capacity may permit re-ignition.
Hazardous combustion	: Hazardous combustion products may include intense heat, dense black smoke, carbon monoxide, carbon dioxide and traces of hydrocarbon fragments.
Conditions of flammability	: Requires a continuous flame source to ignite and sustain burning.
Explosion data	
- Impact sensitivity	: Not sensitive to mechanical impact.
- Static discharge	: Not sensitive to static discharge.

### 6. ACCIDENTAL RELEASE MEASURES

General	: Sweep or gather up material and place in proper container for disposal or recovery (See Disposal Information).
---------	--

### 7. HANDLING AND STORAGE

## KEQI® POLYCARBONATE SHEET

Revision : 27/05/2015, Supersedes issue : 06/02/2002

Page : 3/4

Handling : Follow good standard industrial hygiene practices. Apply adequate ventilation directly to the outside air.

Storage : Inert material under normal storage conditions. No special precautions required.

: Do not stock unsupported sheet or pallets too high.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure controls : A continuous supply of fresh air to the workplace, together with removal of processing fumes through exhaust systems is recommended.

Personal Protection

- Eye/face : Wear safety glasses with side shields when cutting the sheet.
- Respiratory : Good industrial hygiene practice requires adequate general ventilation of the workplace. When dust and powder from secondary operations, such as grinding, sanding or sawing are not adequately controlled, use respirator approved for protection from dust.
- Hands : Wear protective gloves when handling the sheet, as the edges may be sharp.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : Solid

Odour and appearance : Multi-wall plastic sheet with slight or no odour

Boiling point : Not applicable

Melting point : See comment below

Vapor pressure (mmHg) : Negligible

Vapor density (air=1) : Not applicable

Specific gravity (water=1) : >1

Water solubility : Insoluble

% Volatiles : Negligible

pH : Not applicable

Odour threshold : Not established

Evaporation rate : Negligible

Coefficient water/oil distr. : Not established

Flash point : Not applicable

Lower flammable limit : Not established

Upper flammable limit : Not established

Autoignition : 630°C, estimated

Comment : This product does not exhibit a sharp melting point, but softens gradually over a wide temperature range.

### 10. STABILITY AND REACTIVITY

## KEQI® POLYCARBONATE SHEET

Revision : 27/05/2015, Supersedes issue : 06/02/2002

Page : 4/4

Stability : Stable under recommended conditions of storage and handling.  
Reactivity : Not reactive under recommended conditions of handling, storage, processing and use.  
Hazardous : Processing fumes evolved at recommended processing conditions  
Decomposition : may include trace levels of phenol, alkyl phenols and diarylcarbonates.

### 11. TOXICOLOGICAL INFORMATION

Product

- Acute oral : Oral LD50 (rat) > 5 g/kg, estimated.

### 12. ECOLOGICAL INFORMATION

General : Not expected to present any significant ecological problems.

### 13. DISPOSAL INFORMATION

Waste disposal : This product is not regarded as hazardous waste.  
: Dispose in accordance with local regulations.  
Recycling : This product may be recycled either back into sheet, or into other suitable applications.  
: Please consult our sales office for advice.

### 14. TRANSPORTATION INFORMATION

General : This product is not subject to transport regulations.

### 15. REGULATORY INFORMATION

This product is not considered dangerous under EC Directives 67/548/EEC and 88/379/EEC, as amended.

This MSDS has been prepared in accordance with EU Directive 91/155/EEC, as amended by 93/112/EC.

### 16. OTHER

This publication provides information and guidelines for safe handling and cutting of ZHEJIANG AOCI DECORATION MATERIALS CO., LTD's sheet and is based on currently available experience and knowledge. It is not designed as a comprehensive product performance data sheet, nor as a guide to application possibilities of our materials.

Users should follow all applicable local regulations governing Health and Safety at work, and are requested to pass this publication on to all relevant employees and customers.

KEQI® is registered trademarks of the ZHEJIANG AOCI DECORATION MATERIALS CO., LTD. or its affiliates.